



# WOS 550x550 SPLIT VISE BAND SAW MACHINE

\*Photo may feature machine with optional accessories

### **CUTTING CAPACITY**

	0 °
Ø	550 mm
	520 mm
	520 x 550 mm
	320 x 500 mm
	450 x 500 mm (with High Jaws)

### TECHNICAL SPECIFICATIONS

*Main Motor* : 5,5kW

Gearbox : Bevel Helical PKD 3390 High Efficiency

*Hydraulic Motor* : 1,5kW

**Coolant Motor** : 0,18kW

**Conveyor Motor** : 0,25kW

**Swarf Brush Motor** : 0,25kW

Feeding Stroke : 675 mm (Multi Indexing)

Servo Feeder Motor : 750 Watt, 3000 rpm

Blade Speed : 22-100 m/min

**Blade Dimensions** : 5.700 x 41x1,3 mm

Machine Weight : 2.370

*Machine Dimensions* : 1.900 x 3.080 x 2.100 mm

### STANDARD ACCESSORIES

### PLC Control Panel

Only control panel without buttons

Error page

Alarm list

Easy language selection

Easy denomination selection

### 11 Alternative Language

Turkish, English, Deutsch, Italian, French, Spanish, Polish, Korean, Swedish, Russian, Arabic (Different language installable)



50 different works can be saved.

Operator can select all programs or just one line to progress recorded program



karmetal

### Inverter

Provides to adjust blade speed up to workpiece diameter, thickness and hardness.



### Sensible Pressure Adjustment

Provides to adjust bow down pressure.



### Adjustable Bow Down Speed



Pressure, clamping period and clamping time can be adjusted.



### Double Vise



# Adjustable Vise Pressure and Manometer



### Motion Vise Fixed Jaw Piston



### Moveable Guide Arms



# Fast Down Speed Approach



# Hydraulic Blade Tensioning

Tensioning period and tensioning time can be adjusted. So blade does not relax and curve cutting gets prevented.



# Bevel Helical Gearbox



# Blade Bedding with 2 Bearings and Carbide Plate



# Electrical Motorised Swarf Brush



# Bearing Bedding at Wheels



# Swarf Conveyor

Remove swarfs from machine by Motor driven conveyor.

# Double Act Hydraulic Top Clamp



# Servo Driver Bow Switch Tension Switch Electric Cabinet Switch Proximity Switch Levelling Foot Leg Transport Hooks

# 2 mt Roller Table With Top and Side Fixing Bars



# Automatic Stop When;

- > The covers are open
- ➤ Blade is broken
- ➤ Blade tension is low
- ➤ Blade is jammed

# **OPTIONAL ACCESSORIES**

# Laser Line Indicator



# Micro Molecular Coolant System




# High Jaws

The package cutting height is 450 mm by high jaws



# **SAFETY EQUIPMENTS**



01	Cover Switch
02	Lower Limit Switch
03	Upper Limit Switch
04	<b>Shuttle Vice Front Limit Switch</b>
05	<b>Shuttle Vice Rear Limit Switch</b>
06	Vice Switch
07	Hydraulic Blade Tensioning Switch
08	Proximity Switch

### **TERMS**


Delivery (After Receipt of written PO):

Type of Delivery :Exwork

### **WARRANTY CONDITIONS**

The machine is under the warranty of KARMETAL LTD. ŞTİ. For a period of 2 years for mechanical parts, 1 year for electric and electronic parts from the date of purchase. This warranty is subject to all of the terms and conditions listed below:

- 1. This warranty is valid only if the **Warranty Registration Form** is filled in and returned to the manufacturer or its authorized dealer within two months after the date of purchase.
- 2. The obligation of the manufacturer under this warranty shall be limited to repairing or replacing components which proves defective and which our examination shall disclose to our satisfaction to be defective.
- 3. Defects due to improper operation, misuse, neglect, alteration, irregular voltage conditions, inadequate wiring, improper installation (all electrical and electronic components, all electrical motors etc.) and due to accidents or any damage caused by transportation, flood, fire, natural disasters, theft are not included in this warranty and are strictly the responsibility of the purchaser.
- 4. Any part returned to KARMETAL or its authorized dealer under the terms of this warranty shall be on the basis of transportation charges prepaid by the customer and must be accompanied by a record of the machine model code and serial number.
- 5. This warranty does not apply to the following components; band saw blade, blade pressure pads or brackets and blade guide bearings because of being consumables.
- 6. Manufacturer and authorized dealer cannot be blamed within maximum repair period for the material or moral damage. Apart from that act the period as Warranty Conditions and there will not be done any retroactive requirement.



Sakarya 1.OSB 10. St. No:11
Arifiye/Sakarya/TURKEY

Phone: +90 264 276 59 16 Fax: +90 264 276 59 19

www.karmetal.com.tr

sales@karmetal.com.tr

Machine videos are available on:





